

The door doesn't recognize you, Face ID 3 does

FingerTec Face ID 3

Face Recognition System for Door Access



Face ID 3 is FingerTec's advanced face recognition terminal. Building on the facial recognition technology, Face ID 3 uses high quality infrared cameras to scan your facial features and verify your identity. Face ID 3 is designed to cater to the demand for a contactless solution in biometrics recognition, while maintaining its quality performance and high reliability. The slim and stylish design of Face ID 3 is perfect as a door access solution at any office, delivering higher security and a modern look at the same time. Also, stay on top of things when managing Face ID 3 with FingerTec's practical and reliable in-house software.



Contactless Identification

With Face ID 3, all you need is one look, and you're ready to go. Facial recognition makes it easy for you to verify yourself without having to free your hands.



Manage Your Data Easily

Administration is easy with the Ingress software application. Ingress allows you to remotely manage door activity of all connected terminals, while containing time attendance functions for attendance monitoring.



Accurate Verification

Face ID 3 enrolls vivid images of the user and stores them as a large file for a more accurate face verification.



Time Zone Settings

Face ID 3 now has an additional feature of 50 Time Zones for you to control and organize authorized access at your workplace.




Combine Your Verification Methods

Opt for the combination of verification methods to get an added confirmation of identity. A Face + RFID / Password verification leaves almost no room for security breaches!



Multiple Communication Methods

Sync Face ID 3 with a PC using one of the many available connections: TCP/IP, RS232, RS485, USB flash disk or 26-bit Wiegand input-output.



Multi-Verification Methods

You have multiple verification options with Face ID 3. Verify yourself using face, card, or even by password.



Get Your Extra Features Here

Full colour touch screen, short messaging, work codes, photo display after verification. These are among our many additional features that you get to enjoy with Face ID 3.



WEB LINK



Product
• <http://info.fingertec.com/faceid3-1>



Quick Start Guide
• <http://info.fingertec.com/faceid3-2>



Installation Guide
• <http://info.fingertec.com/faceid3-3>



User Guide
• <http://info.fingertec.com/faceid3-4>



Video Guide
• <http://info.fingertec.com/faceid3-5>



Technical Tips
• <http://info.fingertec.com/faceid3-6>



Packaging

Dimension(mm) : 245(L) x 90(W) x 225(H)
Weight : 1.3 kg

For more info:-

PC Mart Sdn Bhd (374159-W)

Kuala Lumpur
TC001 3rd Floor Sungai Wang Plaza,
Jalan Sultan Ismail, 50250 Kuala Lumpur
Tel: 03-2148 7670 Fax: 03-2145 7670


Batu Pahat
4A Jalan Maju, Taman Maju,
83000 Batu Pahat, Johor
Tel: 07-4337 670 Fax: 07-4337 671

Johor Bahru
04-40 Skudai Parade Shopping Complex,
Jalan Skudai, 81300 Skudai, Johor
Tel: 07-558 7670 Fax: 07-558 1671

LAYOUT PLAN


System Communication

for illustration only



Installation Diagram

for illustration only



SPECIFICATIONS

MODEL	Face ID 3
SURFACE FINISHING	Acrylonitrile butadiene styrene (ABS) & acrylic
TYPE OF SCANNER	High resolution infrared camera & RFID antenna
MICROPROCESSOR	800 MHz
MEMORY	256 MB flash memory & 128 MB SDRAM
ALGORITHM	Face BioBridge VX 8.0
PRODUCT DIMENSION (L X W X H), mm	86 x 62 x 218
STORAGE	
• Face templates	400
• Cards	10000
• Transactions	100000
ENROLLMENT & VERIFICATION	
• Methods	Face (1:1, 1:N), card or password
• Verification time (sec)	< 2
• Face	FAR < 0.01%, FRR < 0.1%
CARD TECHNOLOGY	
• RFID: 64-bit, 125kHz	Yes
• MIFARE: MF1S50/S70, 13.56MHz	Made to order
• HID: HID 1325, 26-bit, 125kHz	Made to order
COMMUNICATIONS	
• Method	TCP/IP, RS232, RS485, USB disk (Optional WiFi)
• Baud rates	9600, 19200, 38400, 57600, 115200
• Wiegand	26-bit input and output
OPERATING ENVIRONMENT	
• Temperature (°C)	0 ~ 45
• Humidity (%)	20 ~ 80
• Power input	DC12V 3A
TIME ATTENDANCE	
• Siren	Built-in and external
• Work codes	Yes
• Fast transaction checking	Yes
• Receipt printing	Yes (via RS232)
MULTIMEDIA	
• Greeting voice	Yes
• Display	3.0" 65K color TFT touch screen panel
• Photo-ID	Yes
• Day light saving timer	Yes
ACCESS CONTROL	
• EM lock driving output	DC 12V / relay output
• Alarm output	NO only
• Antipassback	Yes
VOICE / DISPLAY LANGUAGE (TERMINAL)	
	English (Standard), Arabic, Indonesian, Chinese (Traditional), Chinese (Simplified), Cantonese, Vietnamese, Japanese, Spanish, Portuguese (Portugal), Turkish. Other languages are available upon request.



FINGERTEC
www.fingertec.my